Bridman

Tarkett, Inc. FB-50 5-21-85

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Cement Tile

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

Tarkett 50

SECTION I

6/1/81

MANUFACTURER'S NAME: CHICAGO ADHESIVE PRODUCTS CO.	EMERGENCY TELEPHONE NO.: 312-581-1300
ADDRESS (Number, Street, City, State, and ZIP Code): 4658 W. 60th St., Chicago, IL 60629	
CHEMICAL NAME AND SYNONYMS: Asphalt Cutback Tile Cmt	TRADE NAME AND SYNONYMS: FB50
CHEMICAL FAMILY	FORMULA: N/A

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS	30	100 to 150 ppm	FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	240-315°F	SPECIFIC GRAVITY (H_2O=1)	.8767
VAPOR PRESSURE (mm Hg.) Solvent @ 100°F	.42	PERCENT, VOLATILE BY VOLUME (%)	30
VAPOR DENSITY (AIR=1)	4+	EVAPORATION RATE (_____ =1)	1.47
SOLUBILITY IN WATER Negligible			
APPEARANCE AND ODOR	Black with petroleum odor		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used): Tag Closed Cup	FLAMMABLE LIMITS	Lel	Uel
EXTINGUISHING MEDIA: Water, CO_2, Dry Powder, Foam			
SPECIAL FIRE FIGHTING PROCEDURES: In closed areas, use air supplied rescue equipment			
UNUSUAL FIRE AND EXPLOSION HAZARDS			

(Continued on reverse side)

SECTION V · HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: N/A

EFFECTS OF OVEREXPOSURE

EMERGENCY AND FIRST AID PROCEDURES

SECTION VI · REACTIVITY DATA

STABILITY			CONDITIONS TO AVOID
	UNSTABLE		
	STABLE	X	

INCOMPATABILITY *(Materials to avoid)*

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS POLYMERIZATION			CONDITIONS TO AVOID
	MAY OCCUR		
	WILL NOT OCCUR	X	

SECTION VII · SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WASTE DISPOSAL METHOD

COMMERCIAL

SECTION VIII · SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION *(Specify type)*

VENTILATION			
	LOCAL EXHAUST	X	SPECIAL
	MECHANICAL *(General)*		OTHER

PROTECTIVE GLOVES		EYE PROTECTION	
	X		X

OTHER PROTECTIVE EQUIPMENT

SECTION IX · SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Good housekeeping and personal hygiene is indicated. Keep away from heat, sparks and open flame. Use with adequate ventilation. Avoid prolonged or repeated contact with skin.

OTHER PRECAUTIONS

While information and recommendations set forth are believed to be accurate as of the date hereof, CHICAGO ADHESIVE PRODUCTS CO. MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIM ALL LIABILITY FROM RELIANCE HEREON.

GPO 930-340

Form OSHA-20
Rev. May 72