

# MATERIAL SAFETY DATA SHEET



SCM CORPORATION

WEN COATINGS & RESINS DIVISION  
CLID AVENUE  
CLEVELAND, OHIO 44115  
EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

3497

PAGE 1

## SECTION I

CODE IDENTIFICATION 3497 DATE PRINTED 03/14/86  
PRODUCT IDENTIFICATION SPRED SATIN DEEP TINT BASE NO. 7

## SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	WEIGHT PERCENT	THRESHOLD LIMIT VALUE	LEL	VAPOR PRESS.
CALCIUM CARBONATE CAS NO. - 471-34-1	7	10 MG/M3		
HEXYLENE GLYCOL CAS NO. - 107-41-5	1	C 25 PPM	1.2	.10
ALUMINUM SILICATE (CLAY) CAS NO. - 22708-90-3	5	10 MG/M3		
SILICA CAS NO. - 14808-60-7	10	0.1 MG/M3		
TITANIUM DIOXIDE CAS NO. - 1317-80-2	3	10 MG/M3		

C-CEILING - THE CONCENTRATION THAT SHOULD NOT BE EXCEEDED EVEN INSTANTANEOUSLY.

THE THRESHOLD LIMIT VALUE (TLV) IS THE TIME WEIGHTED AVERAGE (TWA) TO WHICH IT IS BELIEVED THAT MOST WORKERS MAY BE EXPOSED 8-10 HOURS PER DAY, 40 HOURS PER WEEK WITHOUT ADVERSE HEALTH EFFECTS.

LEL - THE LOWER EXPLOSIVE LIMIT IS THE LOWEST CONCENTRATION (% OF VOLATILES IN AIR) THAT WILL PRODUCE A FLASH OF FIRE WHEN AN IGNITION SOURCE IS PRESENT.

## SECTION III - PHYSICAL DATA

BOILING RANGE NOT DETERMINED WEIGHT PER GALLON 10.28  
% VOLATILE BY VOLUME 59.54

# MATERIAL SAFETY DATA SHEET



SCM CORPORATION

EN COATINGS & RESINS DIVISION  
CLID AVENUE  
CLEVELAND, OHIO 44115  
EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

3497

PAGE 2

---

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

---

FLASH POINT (SETA) ABOVE 200 F LOWER EXPLOSIVE LIMIT NOT DETERMINED

DOT (PSN) PAINT

HAZARD CLASS NOT RESTRICTED

EXTINGUISHING MEDIA

DRY CHEMICAL OR FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

SPECIAL FIRE FIGHTING PROCEDURES

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.

---

## SECTION V - HEALTH HAZARD DATA

---

ROUTE OF ENTRY INHALATION  
SKIN  
EYES  
INGESTION

EFFECTS OF OVEREXPOSURE

IRRITATION OF EYES, SKIN, RESPIRATORY TRACT. PROLONGED INHALATION MAY LEAD TO MUCOUS MEMBRANE IRRITATION, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, NAUSEA. POSSIBLE DROWSINESS.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION MOVE PERSON TO WELL VENTILATED AREA.  
GET EMERGENCY MEDICAL ATTENTION.  
ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION IF NECESSARY.

SKIN CONTACT FLUSH FROM SKIN WITH WATER, THEN WASH THOROUGHLY WITH SOAP AND WATER.  
REMOVE CONTAMINATED CLOTHING.  
WASH CONTAMINATED CLOTHING BEFORE RE-USE.

# MATERIAL SAFETY DATA SHEET



SCM CORPORATION

EMEN COATINGS & RESINS DIVISION  
JCLID AVENUE  
CLEVELAND, OHIO 44115  
EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

3497

PAGE 3

---

## SECTION V - HEALTH HAZARD DATA

---

EYE CONTACT FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET EMERGENCY MEDICAL ATTENTION.

INGESTION GET EMERGENCY MEDICAL ATTENTION.

---

## SECTION VI - REACTIVITY DATA

---

STABILITY STABLE

INCOMPATIBILITY OXIDIZERS  
ACIDS

CONDITIONS TO AVOID

\*\*\* NOT DETERMINED \*\*\*

HAZARDOUS DECOMPOSITION PRODUCTS

CARBON MONOXIDE  
CARBON DIOXIDE

HAZARDOUS POLYMERIZATION

WILL NOT OCCUR

---

## SECTION VII - SPILL OR LEAK PROCEDURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

ELIMINATE ALL SOURCES OF IGNITION.

VENTILATE AREA.

SMALL SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS.

LARGE SPILLS - OBSERVE STEPS FOR SMALL SPILLS. SHUT OFF

LEAK IF SAFE TO DO SO. DIKE AND CONTAIN SPILL. PUMP TO

STORAGE OR SALVAGE VESSELS. USE ABSORBENT TO PICK UP EXCESS

RESIDUE. KEEP SALVAGE MATERIAL AND RINSE WATER OUT OF SEWERS

OR WATER COURSES. COMPLY WITH ALL APPLICABLE REGULATIONS FOR

HEALTH AND POLLUTION CONTROL.

# MATERIAL SAFETY DATA SHEET



SCM CORPORATION

WEN COATINGS & RESINS DIVISION  
JCLID AVENUE  
CLEVELAND, OHIO 44115  
EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

3497

PAGE 4

---

## SECTION VII - SPILL OR LEAK PROCEDURES

---

WASTE DISPOSAL DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.  
AVOID DISCHARGE TO NATURAL WATERS.

---

## SECTION VIII - SPECIAL PROTECTION INFORMATION

---

### RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE STANDARDS. WHERE RESPIRATORY PROTECTION IS REQUIRED, USE ONLY NIOSH/MSHA APPROVED RESPIRATORS IN ACCORDANCE WITH OSHA STANDARD 29 CFR 1910.134.

### VENTILATION

PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.

### PERSONAL PROTECTIVE EQUIPMENT

EYE WASH  
SAFETY SHOWER  
SAFETY GLASSES OR GOGGLES  
IMPERVIOUS GLOVES

---

## SECTION IX - SPECIAL PRECAUTIONS

---

### HANDLING AND STORAGE

STORE BELOW 100 F.  
KEEP FROM FREEZING.

### OTHER PRECAUTIONS - USE ONLY WITH ADEQUATE VENTILATION. -

DO NOT TAKE INTERNALLY.  
KEEP OUT OF REACH OF CHILDREN.  
AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS.  
WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING.  
KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE.  
AVOID BREATHING SANDING DUST.  
EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES.