List

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURE'S NAME: W. F. Taylor Co., Inc.	EMERGENCY TELEPHONE NO.: (213) 802-1896
ADDRESS (Number, Street, City, State, and ZIP CODE): 13660 Excelsior Drive, Santa Fe Springs, California 90670	
CHEMICAL NAME AND SYNONYMS: Talloil Pitch/Solvent Blend	TRADE NAME AND SYNONYMS: TouchDown #737
CHEMICAL FAMILY:	FORMULA:

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS & METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
Methanol	19	200

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	Unknown	SPECIFIC GRAVITY (H_2O = 1)	1.38
VAPOR PRESSURE (mm Hg.)	Unknown	PERCENT VOLATILE ~~BY VOLUME (%)~~ By Weight	20
VAPOR DENSITY (AIR=1)	Unknown	EVAPORATION RATE (_____ = 1)	
SOLUBILITY IN WATER	Unknown		

APPEARANCE AND ODOR: Thick Brown Mastic - resinous odor

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (Method Used): Less than 100°F.	FLAMMABLE LIMITS	Lel	Uel

EXTINGUISHING MEDIA: Foam, carbon-dioxide, water spray

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, flame or hot metal surfaces

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: Unknown

EFFECTS OF OVEREXPOSURE: May cause light headiness and/or headache from solvent. No hazardous effects when dry.

EMERGENCY AND FIRST AID PROCEDURES

Remove to fresh air - call physician

SECTION VI - REACTIVITY DATA

STABILITY			CONDITIONS TO AVOID
	UNSTABLE		Sparks, open flame, hot
	STABLE	X	metal surfaces

INCOMPATABILITY (Materials to avoid): NONE

HAZARDOUS DECOMPOSITION PRODUCTS: May produce carbondioxide and/or carbon monoxide

HAZARDOUS POLYMERIZATION			CONDITIONS TO AVOID
	MAY OCCUR		
	WILL NOT OCCUR	X	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Contain and mix with sand

WASTE DISPOSAL METHOD: Any approved method - according to applicable laws.

SECTION VII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)

VENTILATION				
	LOCAL EXHAUST	Yes	SPECIAL	NONE
	MECHANICAL (General)	YES	OTHER	

PROTECTIVE GLOVES	EYE PROTECTION
NO	NO

OTHER PROTECTION EQUIPMENT: NO

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep away from sparks, open flame, hot metal surfaces - Do not puncture container.

OTHER PRECAUTIONS: NONE