L1

MATERIAL SAFETY DATA SHEET

Rec 8/86

SECTION I

SAFETY DATA SHEET 1/15/86

PRODUCT NAME OR NUMBER TOUCH 'N FOAM	EMERGENCY TELEPHONE NO. 314-535-6226
MANUFACTURER'S NAME CONVENIENCE PRODUCTS, INC.	MANUFACTURER'S D-U-N-S NO. 09863069
ADDRESS (Number, Street, City, State and Zip Code) 4205 Forest Park Blvd., St. Louis, MO 63108	
HAZARDOUS MATERIALS DESCRIPTION AND PROPER SHIPPING NAME(49 CFR 172.101) Polyurethane Foam	HAZARD CLASS (49 CFR 172.101) Class 55
CHEMICAL FAMILY Aromatic Polyurethane Isocyanate Prepolymer	FORMULA N/A

SECTION II — INGREDIENTS (list all ingredients)

(HAZARDOUS AND NON HAZARDOUS INGREDIENTS)	CAS REGISTRY NO.	% wt.
Diphenylmethane Diisocyanate (MDI)	26447-40-5	15-20
Chlorinated Phosphate Ester	N/A	10-20
Dichlorodifluoromethane	75-71-8	30-40
Dimethylether	115-10-6	1-10

SECTION III — PHYSICAL DATA

BOILING POINT (X °F) (°C)	-17.1	SPECIFIC GRAVITY (H_2O=1) at 25°C	1.11		
VAPOR PRESSURE (mm Hg) [X] at 25°C (psi) [ ]	4000	PERCENT VOLATILE BY VOLUME (%)	40		
VAPOR DENSITY (AIR=1)	3.9	EVAPORATION RATE (=1)	N/A		
SOLUBILITY IN WATER	Reacts	pH= Neutral			

APPEARANCE AND ODOR Gel under pressure/Faint ether-like odor	IS MATERIAL: [LIQUID] SOLID GAS PASTE POWDER

SECTION IV-FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (method used) (°F) (°C) Not Established	FLAMMABLE LIMITS	LEL N/A	UEL N/A

EXTINGUISHING MEDIA
Dry chemical, CO_2, High expansion chemical foam, water spray

SPECIAL FIRE FIGHTING PROCEDURES
Fire fighters should wear full self-contained breathing apparatus and full protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS
Avoid storage temperatures above 120°F to prevent can explosions. Avoid water contamination in closed containers.

SECTION V-HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE May cause respiratory discomfort and allergic reactions. Symptoms asthma-like in nature.	THRESHOLD LIMIT VALUE [X] 0.02 ppm PERMISSIBLE EXPOSURE LIMIT [ ]

EMERGENCY AND FIRST AID PROCEDURES