MAMECO INTERNATIONAL, INC.

MATERIAL SAFETY DATA SHEET

REVISION DATE 11-7-85

MANUFACTURER MAMECO INTERNATIONAL; 4475 E. 175TH ST.; CLEVELAND, OH 44128 **EMER. PHONE NO.** 216-752-4400

SECTION 01 IDENTIFICATION OF PRODUCT

TRADE NAME & SYNONYMS Vulkem 116 **MSDS/PRODUCT NUMBER** 605031000

PRODUCT CLASS Polyurethane Sealant

SECTION 02 HAZARDOUS COMPONENTS OF MIXTURES

COMPONENTS	PERCENT	THRESHOLD LIMIT VALUE	COMPONENTS	PERCENT	THRESHOLD LIMIT VALUE
Aromatic Petroleum Solvent	5%	50 ppm			
Aromatic Isocyanates	<0.5%	0.02 ppm			

SECTION 03 PHYSICAL DATA

BOILING RANGE N/A

VAPOR DENSITY Heavier than Air

WEIGHT PER GALLON 10.0 Lbs./Gal.

PERCENT VOLATILE 14.0% by Volume

EVAPORATION RATE Slower than Ether

SECTION 04 FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY Combustible Liquid

FLASH POINT 150°F.

FIRE EXTINGUISHING MEDIA Waterspray. waterfog, dry chemical Co_2, foam

SPECIAL FIRE FIGHTING PROCEDURE Wear goggles, self contained breathing apparatus, and full protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS Fire: Moderate when exposed to heat. Explosion: Moderate when vapor is exposed to heat or flame. Toxic gases may occur as decomposition products. Reaction with water produces carbon dioxide which could cause pressure build up in a confined container.

SECTION 05 HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE N/A

EFFECTS OF OVER EXPOSURE Causes slight eye and skin irritation. Pulmonary sensitization can occur in some individuals leading to asthma type spasms.

EMERGENCY FIRST AID PROCEDURE Avoid skin contact. If on skin: Thoroughly wash exposed area with soap and water. If in eyes: Flush with large amounts of water. Get medical attention. If swallowed: Do not induce vomiting; get medical attention. If vapors are inhaled: Remove to fresh air. If necessary, administer oxygen and/or artificial respiration. Call a physician.

Cover offer

MAMECO INTERNATIONAL, INC.

MATERIAL SAFETY DATA SHEET

REVISION DATE

TRADE NAME & SYNONYMS Vulkem 116

MSDS/PRODUCT NUMBER 605031000

SECTION 06 REACTIVITY DATA

STABILITY: **STABLE** X **UNSTABLE**

CONDITIONS TO AVOID See Section 9

INCOMPATABILITY Water, alcohol, strong oxidizing agents, strong acids, strong bases.

HAZARDOUS DECOMPOSITION Nitrogen oxides, hydrogen cyanide, carbon monoxide, carbon dioxide.

HAZARDOUS POLYMERIZATION Will not occur.

SECTION 07 SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Allow to harden, scrape up.

WASTE DISPOSAL METHOD Incinerate or landfill in accordance with local, state, and federal environmental regulations.

SECTION 08 SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION Use with adequate ventilation. Respirators with organic vapor cartridges or self contained breathing apparatus may be used in confined areas.

VENTILATION Local exhaust or general mechanical sufficient to prevent accumulation of fumes.

PROTECTION GLOVES Wear resistant gloves such as BUNA-N, plastic, or rubber.

EYE PROTECTION Goggles

OTHER PROTECTIVE EQUIPMENT Protective clothing to prevent skin contact.

RAJ
11/11/85

SECTION 09 SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING & STORING Protect containers from physical damage. Keep container closed when not in use. For safety, store at temperature not exceeding 180°F. away from sparks or flame. For maximum storage life store at less than 90°F. Do not breathe vapors. Avoid skin and eye contact. Do not take internally.

THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, REPRESENTATION, INDUCEMENT OR LICENSE OF ANY KIND, EXCEPT THAT IT IS ACCURATE TO THE BEST OF MAMECO INTERNATIONAL'S KNOWLEDGE OR OBTAINED FROM SOURCES BELIEVED BY MAMECO INTERNATIONAL TO BE ACCURATE. MAMECO INTERNATIONAL ASSUMES NO LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON THESE DATA.